Original/Duplicate/Triplicate
CONTRACT CERTIFICATE

SBRN0: 42/23 98 18

(For Other Works)

Date.....2018

N First & Part Bill

Division: **BBMP, Byatarayanapura** Sub-Division: **BBMP, Vidyaranyapura**

Bill Received No. Dated Divisional / Sub Divisional Cash Book Voucher No..... Dated.....

Work Code: 009-18-000008, 009-18-000006, 010-18-000028

Schedule Docket No. Head of Account: **P-3111** **Est.Cost: 210.00 Lakhs** D.R.No. :

Name of Work (as per sanctioned estimate: Package - 7, Including 2 Works of Rs. 210.00 Lakhs (1) PROVIDING AND FIXING WOODEN FLOORING, PLAY EQUIPMENT, MULTI PURPOSE GYM EQUIPMENTS, BADMITON COURT, TABLE TENNIS STAND, YOGA MATT AND OTHER FITTINGS AT INDOOR STADIUM, VIDYARANYAPURA IN WARD NO. 09 (VIDYARANYAPURA), VIDYARANYAPURA SUB DIVISION. (2) IMPROVEMENTS TO BALANCE ROADS AND DRAINS AT CHAMUNDESHWARI LAYOUT, NANJAPPA LAYOUT AND SURROUNDING AREAS IN WARD NO. 10 (DODDABOMMASANDRA), VIDYARANYAPURA SUB DIVISION.

Name of Contractor and Full Address: ***M/S Soorya Creators, Sri P. Hemanth, # 109/110, 4th Cross, 6th Main, Vivekananda Road, Balaji Layout, R.M.V 2nd Stage, Bangalore - 94.***

Reference to Agreement No. **BBMP/EE/BTP/M.WO/82/2018-19** Date: 13-08-18

Certified that the measurements were taken by me on 13/08/2018 and recorded of **Pages** 357756 **to** 357761/2 of measurement Book No. 3578/2017-18 and that the work is satisfactorily executed.

P. Hemanth 13/8/2018

Contractor **Officer-in-charge of work**

Certified that the measurement were taken by me on 13/8/2018 .....and found correct. The work is satisfactorily executed.

Certified that the quantities of materials shown in column 3 of Account have been actually brought to site of the work and the contractor has not previously received any advance on this security. These materials are of and imperishable nature and are all required for immediate use on the work in connection with items for finished work have been agreed upon. A normal agreement signed and executed by the contractor is recorded in the office.

Sub-Division Officer

Assistant Executive Engineer
Vidyaranyapura Sub Division
BBMP, Bangalore - 97

II Memorandum of Payment

1)	Total value of work done or supplies made as per account within	
2)	Deduct amount to be held in reserve being .....percent Rs.....	
3)	" Balance	
4)	Deduct Payment:	
	a. Amount of previous payment as in the Office Cash Book Voucher No.....Dated.....S.D. No.....Nil	Amount 1.57.15,980-00
	adjusted towards cash advance recovery of	IT- 314320-00
	b. Payments Now made { cost store or other material supplied.	Cem. 15716-00
	{ recovery of amount creditable to this/other work	CBF- 15716-00
	{ Amount paid on this bill Cheque / Cash.	LR- 032876-00
5)	Balance being unpaid value of work done held in reserve.	
6)	Deduct cash advance made on the Office cash Book Voucher No..... dated.....less adjustments.	
7)	Net amount due to or from Contractor unadjustments items.	Adju- 520072-00
8)	Advance to Contractor for materials brought to site (as detailed) within.	
9)	Value of Government materials supplied.	Cheque 1.57,95908-00
	Total amount adjusted	

Contractor's Signature

Received Rs..... (in words).....

.....

by cash and by adjustment of Payment as per memorandum

(in final settlement of all demands)

Witness
1.
2.

Dated Signature of Contractor

Paid by me by Cheque No.....Dated.....

Cash Rs.....

Dated.....

Initials of Officer making payment

15715980
5,20,072-00 (For use in the Office)
1,57,95,908-00
Rs: One Crore fifty seven lakh ninety five thousand nine hundred eight only.
Stamp
Executive Engineer
23/08

Scanned by CamScanner

Sl. No.		Unit	
20	Supplying and fixing fitness related equipments of approved make and international standards including the cost of equipments, transportation, installation at given location etc., complete **Spin bike :** Providing and fixing of spin bike (GP-333) as per Engineer in Charge of the work. Machine design features proven biomechanics and advanced structural engineering. Quick start key allows commencing exercise with a touch of button. Challenging resistance levels to help you meet your itness goals. Constant heart rate display keeps in the desired training for progressive cardio improving and weight loss. Low maintenance design delivers a fast return of investment. Rotating parts have high quality bearings, are durable in use and there is no noise while using. Heavy gauge welded steel construction. Stayht GP 333 upright bike boasts a beautiful metallic coat inish on a frame of size Dimension 1 5O" (L) X 25"(VV) X 56"(H) Drive System 2 Centre design drive, super silent poly-V belt driven. Pedals 1 Self balanced extra wide pedals with adjustable straps tit to any size user, close spacing , shock Absorbing, air cushion and provides gentle movements. Seat 2 Ergonomically designed comfortable seat with flex cushion with 29 levels seat adjustment.	No	
22	Cross Trainer : Providing and fixing of Elliptical Cross Trainer (GP-666) - Easier, Il/lore effective Cardio. Stayitl Elliptical Cross Trainer GP- 666 provides a natural, low-impact stride, so users can work out longer and harder. And our design lets them target various muscle groups just by changing the resistance levels. Completely smooth and natural feel Reduces joint stress and minimizes fatigue. Moving handlebars for a total-body workout of Dimension : 8O" (L) X 28"(W) X 7O"(H); Strides 1 20 Inches natural strides. Maximum Watt 1 250 Watts; Resistance Level i 161 Levels. Resistance System 3 Electro-Magnetic resistance; Power I Self generated power system; Programs ; O6 Programs - manual, HRC, random, weight loss, CV and hill interval	No	
23	**Tread Mill** : Providing and fixing of Motorised Tread Mill (GP-999) is built for the long run. Our gola was to build treadmill that people would want to use instead of running outside, even if weather conditions were perfect. Ouri engineers have built a revolutionary treadmill that's fully-loaded with patented technology and exclusive performance; features. Our treadmills are powerful running, walking, and jogging machines that are the top choice among exercise enthusiasts around the world. From the basic to the ultimate corporate/club use model, there's nothing like training on a STAYFIT Commercial Series. Stayit treadmills are built to perform to the scrutinizing standards of commercial health club equipment. Compare the features of these extraordinary machines, and you'll discover the qualities that make Stayht the premier name in cardio Htness. Flex Deck Cushioning System - The durable flex deck cushioning system delivers proportional cushioning effects regardless of while using Treadmill. Large Running Surface - The W22" xL 62" running surface provides ample space and is constructed from carbon weave, low friction material that is resistant to static build-up. Powerful Motor - The powerful AC 3.0 HP continuous / 6 HP Peak motor self-cools and self-cleans providing commercial-	No	
24	**Recumbent** : Providing and fixing of recumbent bike(GP-333) as per Engineer in Charge of the work. Machinel design features proven biomechanics and advanced structural engineering. Quick start key allows commencingj exercise with a touch of button. Challenging resistance levels to help you meet your fitness goals. Constant heart rate-I display keeps in the desired training for progressive cardio improving and weight loss. Low maintenance design delivers a fast return of investment. Rotating parts have high quality bearings, are durable in use and there is no noise while using. Heavy gauge welded steel construction. Staytit GP 333 upright bike boasts a beautiful metallic coat finish on a frame of size Dimension I 5O" (L) X 25"(W) X 56"(H) Drive System 1 Centre desigm drive, super silent poly~V belt driven. Pedals ; Self balanced extra wide pedals with adjustable straps it to any size user, close spacing , shock Absorbing, air cushion and provides gentle movements. Seat 3 Ergonomically designed. comfortable seat with flex cushion with 29 levels seat adjustment. Handle Bars 1 U-Bar style with ergonomically elbow support pad and in-built contact heart rate sensors with hand grips. Centre of Gravity 1 Low COG combined with a balanced frame prevents rocking. Cardio Monitor 1 In~built hand grip pulse sensor provided with handle grips enables to the cardio monitoring on board. Display 2 Computerized console.	No	
25	Dumbbells 20.00/kgs		
26	17.50/kgs		
27	15.00/kgs		
28	12.50/kgs	kgs	
29	10.00/kgs	kgs	
30	7.50/kgs	kgs	
31	5.00/kgs	kgs	
32	2.50/kgs	kgs	
33	Dumbbell stand : Providing and fixing Dumbbells rack for easy racking and unrocking ., ideal for larger dumbbelh sets easy for pic and place it back hardchorme dumbbells coated with rubber coating for better life and safety with 137cm x47cmx87cm As per engineer incharge of work.	kgs	
34	Weights stand :Providing and fixing Plate Rack stand of approved make for easy racking and unracking, with rubber coating for better life and safety as per engineer incharge of work	No	
		No	

Scanned by CamScanner

Previous Measurement		Present Measurement			Total Upto Date		Remarks
Qty.	Cost	Qty.	Rate Rs. P.	Amount	Qty	Cost	
-	-	3.00	50400.00	151200.00	3.00	151200.00	
-	-	4.00	140000.00	560000.00	4.00	560000.00	
-	-	4.00	162400.00	649600.00	4.00	649600.00	
-	-	2.00	50400.00	100800.00	2.00	100800.00	
-	-	80.00	168.00	13440.00	80.00	13440.00	
-	-	70.00	168.00	11760.00	70.00	11760.00	
-	-	60.00	168.00	10080.00	60.00	10080.00	
-	-	50.00	168.00	8400.00	50.00	8400.00	
-	-	40.00	168.00	6720.00	40.00	6720.00	
-	-	30.00	168.00	5040.00	30.00	5040.00	
-	-	20.00	168.00	3360.00	20.00	3360.00	
-	-	10.00	168.00	1680.00	10.00	1680.00	
-	-	2.00	28000.00	56000.00	2.00	56000.00	
-	-	2.00	28000.00	56000.00	2.00	56000.00	

Scanned by CamScanner

Sl. No		Unit
35	Multi Press ; Providing and fixing the equipments rigid body structure plays a critical role in the machine superb handling Dimensions 3 93"(L) x 44" (W) x 42" (H). Frame 3 High tensile strength steel, continuous welded, factory; assembled weight frame. Tube 1 capsule Tube Size 1 80mm x 50mm main frame. Tube Gauge 1 3.0 mm. Weight Stack 1 80 Kgs Weight Plate 1 Cast iron, machine drilled to exact spec and employ oversized nylon bushings forl super-smooth operations. Weight Stack Guard 1 Full front and rear shields. Weight Guide Rods 1 22 mm, chromei 2 plated solid steel, highly policed for smooth movements. Weight Selector Rod 1 25 mm, chrome plated highly policed for smooth movements. Weight Selector Pin 1 10 mm gauge steel pin with magnetic knob. Cable 1 Steel Cablef 3.5mm Jacked with PVC 5.5mm outside diameter Pulley S Nylon, 106 mm x 20 mm diameter with Sealed bearing.§ Grips 1 Multiple gripping positions, high density rubber hand grips. Finishing 1 Proprietary two coat powder process!Rust Proof: Electro statically applied powder coated. Frame Color: Grey.	No
36	Lat Pull down : Providing and fixing the equipments rigid body structureplays a critical role in the machine superb, handling Dimensions 1 93"(L) x 44" (W) x 42" (H). Frame 1 l-ligh tensile strength steel, continuous welded, factorw assembled weight frame. Tube 3 capsule Tube Size 2 80mm x 50mm main frame Tube Gauge 3 3.0 mm. Weight! Stack : 80 Kgs Weight Plate ; Cast iron, machine drilled to exact spec and employ oversized nylon bushings forf super-smooth operations. Weight Stack Guard 1 Full front and rear shields. Weight Guide Rods I 22 mm, chrome plated solid steel, highly policed for smooth movements. Weight Selector Rod I 25 mm, chrome plated highly policed for smooth movements. Weight Selector Pin 3 10 mm gauge steel pin with magnetic knob. Cable 3 Steel Cable 3.5mm Jacked with PVC 5.5mm outside diameter. Pulley 1 Nylon, 106 mm x 20 mm diameter with Sealed bearing Grips 3 Multiple gripping positions, high density rubber hand grips. Finishing 1 Proprietary two coat powder process Rust Proof: Electro statically applied powder coated.	No
37	Mid row : Providing and fixing an equipment of dimensions 93" X 44" X 42" _ Frame 1 High tensile strength steel, continuous welded, factory assembled weight frame. Tube 1 Capsule of size 80mm x 50mm main frame with 3mm gauge. Weight stack 1 80 Kgs , Weight plate 1 Cast iron, machine drilled to exact spec and employ oversized nylon bushing for super smooth operations. Weight stack guard 1 full front and rear shields. Weight guide rods 1 22 mm, chrome plated solid steel, highly polished for smooth movements, Weight selector rod ; 25mm, chrome plated highly polished for smooth movements, weight selector pin 10mm gauge steel pin magnetic knob, Cable 3 steel cable of 3.5mm jacked with PVC 5.5 mm outside diameter, Pulley 1 Nylon 106mm x 20mm diameter with sealed bearing. Grips 1 Multiple gripping positions, high density rubber hand grips, finishing 3 Proprietary two coat powder process, Rust proof 1 Electro statically applied powder coated. Frame color 1 Grey. Workouts 3 Peres major latissimus dorsi, ramboid major as per Engineer in Charge of the work.	No

Scanned by CamScanner

Previous Measurement		Present Measurement			Total Upto Date		Remarks
Qty.	Cost	Qty.	Rate Rs. P.	Amount	Qty	Cost	
-	-	1.00	106400.00	106400.00	1.00	106400.00	
-	-	1.00	112000.00	112000.00	1.00	112000.00	
-	-	1.00	112000.00	112000.00	1.00	112000.00	

Scanned by CamScanner

Sl. No.		
38	Shoulder Press: Providing and fixing the equipments rigid body structure plays a critical role in the machine superb handling Dimensions : 93"(L) x 44" (W) x 42" (H). Frame 1 High tensile strength steel, continuous welded, factory assembled weight frame. Tube 1 capsule Tube Size 1 80mm x 50mm main frame. Tube Gauge 5 3.0 mm. Weight Stack 1 80 Kgs Weight Plate 1 Cast iron, machine drilled to exact spec and employ oversized nylon bushings for super-smooth operations. Weight Stack Guard 1 Full front and rear shields. Weight Guide Rods 1 22 mrn, chrome plated solid steel, highly policed for smooth movements. Weight Selector Rod 1 25 mm, chrome plated highly policed for smooth movements. Weight Selector Pin 1 10 mm gauge steel pin with magnetic knob. Cable 1 Steel Cable 3.5mm Jacked with PVC 5.5mm outside diameter. Pulley 1 Nylon, 106 mm x 20 mm diameter with Sealed bearing. Grips 1 Multiple gripping positions, high density rubber hand grips. Finishing 1 Proprietary two coat powder process. Rust Proof: Electro statically applied powder coated. Frame Color 1 Grey.	N
39	Leg Press : Providing and fixing the equipments rigid body structure plays a critical role in the machine superb handling Dimensions 1 93"(L) x 44" (W) x 42" (H). Frame 1 High tensile strength steel, continuous welded, factory assembled weight frame. Tube 1 capsule Tube Size 1 80mm x 50mm main frame. Tube Gauge 1 3.0 mm. Weight Stack 1 80 Kgs Weight Plate 1 Cast iron, machine drilled to exact spec and employ oversized nylon bushings for super-smooth operations. Weight Stack Guard 1 Full front and rear shields. Weight Guide Rods 1 22 mm, chrome plated solid steel, highly policed for smooth movements. Weight Selector Rod i 25 mm, chrome plated highly policed for smooth movements. Weight Selector Pin 1 10 mm gauge steel pin with magnetic knob. Cable 1 Steel Cable 3.5mm Jacked with PVC 5.5mm outside diameter. Pulley 1 Nylon, 106 mm x 20 mm diameter with Sealed bearing. Grips 1 Multiple gripping positions, high density rubber hand grips. Finishing 1 Proprietary two coat powder process. Rust Proof: Electro statically applied powder coated. Frame Color: Grey.	No
40	**Leg Extension**: Providing and fixing the equipments rigid body structure plays a critical role in the machine superb handling Dimensions 1 93"(L) x 44" (W) x 42" (H). Frame 1 High tensile strength steel, continuous welded, factory assembled weight frame. Tube 1 capsule Tube Size 1 80mm x 50mm main frame. Tube Gauge 1 3.0 mm, Weight Stack 1 80 Kgs Weight Plate 1 Cast iron, machine drilled to exact spec and employ oversized nylon bushings for super-smooth operations. Weight Stack Guard 1 Full front and rear shields, Weight Guide Rods 1 22 mm, chrome plated solid steel, highly policed for smooth movements. Weight Selector Rod 1 25 mm, chrome plated highly policed for smooth movements. Weight Selector Pin 1 10 mm gauge steel pin with magnetic knob. Cable 1 Steel Cable 3.5mm Jacked with PVC 5.5mm outside diameter Pulley 1 Nylon, 106 mm x 20 mm diameter with Sealed bearing. Grips 1 Multiple gripping positions, high density rubber hand grips. Finishing L Proprietary two coat powder process. Rust Proof 1 Electro statically applied powder coated. Frame Color 1 Grey.	No
41	**Leg Curl** : Providing and fixing the equipments rigid body structure plays a critical role in the machine superb handling Dimensions 1 93"(l_) x 44" (W) x 42" (H). Frame 1 High tensile strength steel, continuous welded, factory assembled weight frame. Tube 1 capsule Tube Size 1 80mm x 50mm main frame. Tube Gauge 1 3.0 mm. Weight Stack 1 80 Kgs Weight Plate 1 Cast iron, machine drilled to exact spec and employ oversized nylon bushings for super-smooth operations. Weight Stack Guard 1 Full front and rear shields. Weight Guide Rods 1 22 mm, chrome plated solid steel, highly policed for smooth movements. Weight Selector Rod 1 25 mm, chrome plated highly policed for smooth movements. Weight Selector Pin 1 10 mm gauge steel pin with magnetic knob. Cable 1 Steel Cable 3.5mm Jacked with PVC 5.5mm outside diameter. Pulley 1 Nylon, 106 mm x 20 mm diameter with Sealed bearing. Grips 1 Multiple gripping positions, high density rubber hand grips. Finishing 1 Proprietary two coat powder process. Rust Proof 3 Electro statically applied powder coated. Frame Color 1 Grey.	No

Scanned by CamScanner

...al/Duplicate ... CERTIFICATE ... Date

Previous Measurement		Present Measurement			Total Upto Date		Remarks
Qty.	Cost	Qty.	Rate Rs. P.	Amount	Qty	Cost	
-	-	1.00	106400.00	106400.00	1.00	106400.00	
-	-	1.00	134400.00	134400.00	1.00	134400.00	
-	-	1.00	100800.00	100800.00	1.00	100800.00	
-	-	1.00	100800.00	100800.00	1.00	100800.00	

Scanned by CamScanner

Sl. No.		Unit
42	**Smith Machine :** Providing and fixing the equipments rigid body structure plays a critical role in the machine superb handling Dimensions 1 93"(t.) x 44" (W) x 42" (H). Frame 1 High tensile strength steel, continuous welded, factory assembled weight frame Tube 1 capsule Tube Size 1 80mm x 50mm main frame. Tube Gauge 1 3.0 mm. Weight Stack 1 80 Kgs Weight Plate 1 Cast iron, machine drilled to exact spec and employ oversized nylon bushings for super-smooth operations. Weight Stack Guard 1 Full front and rear shields. Weight Guide Rods 1 22 mm, chrome plated solid steel, highly policed for smooth movements. Weight Selector Rod 1 25 mm, chrome plated highly policed for smooth movements. Weight Selector Pin 1 10 mm gauge steel pin with magnetic knob. Cable 1 Steel Cable 3.5mm Jacked with PVC 5.5mm outside diameter, Pulley 1 Nylon, 106 mm x 20 mm diameter with Sealed bearing. Grips 1 Multiple gripping positions, high density rubber hand grips. Finishing 1 Proprietary two coat powder process. Rust Proof; Electro statically applied powder coated. Frame Color 1 Grey.	No
43	**Pectorial fly machine** : Providing and fixing fly machine with overall dimension 46" x 65" x 55" proprietary two coat powder process, internally lubricated cables, full front and rear weight stack guarding sheets, total stack weight of 110 kg, as per standard specification and direction from the Engineer in charge.	No
44	Oblique rear fly machine : Providing and fixing oblique rear fly machine of size 56" x 54" x 76", frame 1 using high quality steel tube with 125/50 flat elliptical tube or equivalent of guage 3_0 mm, Cable 1 Solid steel wire capable of bearing 1500 Kg, Guide Rod 1 No 45 steel handled by high frequency, hardness, precision to ensure user's safety. Weight Stack 3 92 Kgs, painting 1 powder coating double layer of high quality colour powder.	No
45	**Assisted Chinup** : Providing and fixing excellent range of 75 kgs weight assisted chinup of 72" x 42" x 88", Frame 1 using high quality steel tube of 120/50 flat elliptical tube or equivalent of guage 3.0 mm, Cable 2 Solid steel wire capable of bearing 1500 Kg, Guide Rod 1 No 45 steel handled by high frequency, hardness, precision to ensure user's safety. Weight Stack 1 92 Kgs, painting 1 powder coating double layer of high quality colour powder.	No
46	**Bench press** - declined The equipments rigid body structure plays a critical role in the machine superb handling Dimensions 1 93"(t_) x 44" (W) x 42" (H). Frame 1 High tensile strength steel, continuous welded, factory assembled weight frame. Tube 1 capsule Tube Size 1 80mm x 50mm main frame. Tube Gauge 1 3.0 mm. Weight Stack 1 80 Kgs Weight Plate 1 Cast iron, machine drilled to exact spec and employ oversized nylon bushings for super-smooth operations. Weight Stack Guard 1 Full front and rear shields. Weight Guide Rods 1 22 mm, chrome plated solid steel, highly policed for smooth movements. Weight Selector Rod 1 25 mm, chrome plated highly policed for smooth movements. Weight Selector Pin 1 10 mm gauge steel pin with magnetic knob. Cable 3 Steel Cable 3.5mm Jacked with PVC 5.5mm outside diameter. Pulley 1 Nylon, 106 mm x 20 mm diameter with Sealed bearing. Grips 1 Multiple gripping positions, high density rubber hand grips. Finishing 1 Proprietary two coat powder process. Rust Proof 2 Electro statically applied powder coated. Frame Color 1 Grey.	No

Scanned by CamScanner

Previous Measurement		Present Measurement			Total Upto Date		Remarks
Qty.	Cost	Qty.	Rate Rs. P.	Amount	Qty	Cost	
-	-	1.00	168000.00	168000.00	1.00	168000.00	
-	-	1.00	100800.00	100800.00	1.00	100800.00	
-	-	1.00	100800.00	100800.00	1.00	100800.00	
-	-	1.00	128800.00	128800.00	1.00	128800.00	
-	-	2.00	44800.00	89600.00	2.00	89600.00	

Scanned by CamScanner

Sl. No.		Unit
47	**Bench press** - inclined The equipments rigid body structure plays a critical role in the machine superb handling Dimensions 3 93"(l_) x 44" (W) x 42" (H). Frame 1 High tensile strength steel, continuous welded, factory assembled weight frame. Tube ; capsule Tube Size 3 80mm x 50mm main frame. Tube Gauge 1 3.0 mm. Weight Stack ; 80 Kgs Weight Plate 1 Cast iron, machine drilled to exact spec and employ oversized nylon bushings for super-smooth operations. Weight Stack Guard 1 Full front and rear shields. Weight Guide Rods 1 22 mm, chrome plated solid steel, highly policed for smooth movements. Weight Selector Rod 1 25 mm, chrome plated highly policed for smooth movements. Weight Selector Pin 1 10 mm gauge steel pin with magnetic knob. Cable 1 Steel Cable 3.5mm Jacked with PVC 5.5mm outside diameter. Pulley 1 Nylon, 106 mm x 20 mm diameter with Sealed bearing. Grips 1 Multiple gripping positions, high density rubber hand grips. Finishing 1 Proprietary two coat powder process. Rust Proof 1 Electro statically applied powder coated. Frame Color 1 Grey. Workouts 2 Teres major latissimus dorsi, Ramboid Major as per Engineer in Charge of the work.	No
48	**Bench press** - tlat, with the above same specihcation	No
49	**Bar bell** : Providing and supplying barbell of approved make as per the instruction of the Engineer in Charge. (i) 7 feet barbell	No
50	(ii) 5 feet barbell	No
51	(iii) 3 feet barbell	No
52	(iv) kettler barbell	No
53	**Barbel stand** : Providing and supplying barbel stand of approved make as per specification.	No
54	**Weights** : Providing and supplying weights of approved make as per the instruction ofthe Engineer in Charge. 20.00/kgs	kgs
55	15.00/kgs	kgs
56	10.00/kgs	kgs
57	7.50/kgs	kgs
58	5.00/kgs	kgs
59	2.50/kgs	kgs
60	1.25/kgs	kgs
61	**Abodomen mats** : Providing mats for abdomen workouts made from premium quality PVC fabrics that ensures its longivity and durability, the mat should be smooth and even finished. i)Long mats - 68" x 24"	
62	ii)Short mats - 48" x 24"	No
63	Providing and laying of modular wooden polished flooring of 12 mm thick, high density timber of approved colour and design with end trims, transition, profiles, beading, 15 mm thick felt, and 20 micron polyster Elm with 4mm thick foam underlay etc.,	Sqm
64	Providing and constructing standard rubber flooring for indoor area uising rubber membren of 12mm to 16mm thick,to be layed over prepared cement mortor /concrte surface using cm 1:6 beneath rubber membrane including cost of all materials ,labour ,packing joints and mortor Hnishing curing ,all lead and lift ,transportion and also including all applicable taxes complete as per direction incharge of work.	Sqm
65	Providing venyl flooring of approved quality and make, tixed on the top of existing flooring tixed with suitable adeshive, including cutting to the required size and fixing etc, complete	Sqm
66	**Table Tennis** : Supplying and installing Table tennis board approved make,standard size including all the cost transportation, installation etc., complete Tables - (3O`-0" X 16'-6")	No
67	Bats - standard size	No
68	Balls	No
69	**Badminton** : Supplying and installing Shuttle court related equipments including Fixing of poles, nets etc., complete as per specification Net- 2'-0" high	
70	Poles - 5'-1" high	No
71	Shuttle racket- Standard size	No
72	shuttle cock	No
73	**Yoga Mats** :Providing mats for yoga made from premium quality PVC fabrics that ensures its longivity and durability the mat should be smooth and even finished. Mats - 68" long x 24" wide	No
74	Providing and setting up of a children play yard including all the equipments	No

Scanned by CamScanner

Previous Measurement		Present Measurement			Total Upto Date		Rema
Qty.	Cost	Qty.	Rate Rs. P.	Amount	Qty	Cost	
-	-	2.00	44800.00	89600.00	2.00	89600.00	
-	-	2.00	28000.00	56000.00	2.00	56000.00	
-	-	4.00	11200.00	44800.00	4.00	44800.00	
-	-	4.00	8400.00	33600.00	4.00	33600.00	
-	-	4.00	5600.00	22400.00	4.00	22400.00	
-	-	4.00	8400.00	33600.00	4.00	33600.00	
-	-	2.00	44800.00	89600.00	2.00	89600.00	
-	-	60.00	195.00	11700.00	60.00	11700.00	
-	-	45.00	196.00	8820.00	45.00	8820.00	
-	-	30.00	196.00	5880.00	30.00	5880.00	
-	-	45.00	196.00	8820.00	45.00	8820.00	
-	-	50.00	196.00	9800.00	50.00	9800.00	
-	-	25.00	196.00	4900.00	25.00	4900.00	
-	-	7.50	196.00	1470.00	7.50	1470.00	
-	-	1.00	1680.00	1680.00	1.00	1680.00	
-	-	5.00	1120.00	5600.00	5.00	5600.00	
-	-	1350- 1356.00	3442.88	4647808- 4668545.00	1350- 1356.00	4647808- 4668545.00	
-	-	318.07	5423.04	1724906.00	318.07	1724906.00	
-	-	814.04	618.80	503728.00	814.04	503728.00	
-	-	3.00	28000.00	84000.00	3.00	84000.00	
-	-	12.00	1008.00	12096.00	12.00	12096.00	
-	-	36.00	28.00	1008.00	36.00	1008.00	
-	-	2.00	28000.00	56000.00	2.00	56000.00	
-	-	4.00	2800.00	11200.00	4.00	11200.00	
-	-	8.00	1680.00	13440.00	8.00	13440.00	
-	-	15.00	168.00	2520.00	15.00	2520.00	
			448.00	11200.00	25.00	11200.00	

Scanned by CamScanner

Sl. No.	
75	Providing and supplying commercial RO plant of 100 LPH capacity water purifier system suitable for TDS upto 1500 PPM, multiple purification process, suitable to attend with water cooler, finally automatic optional storage tank box pack of approved make and standards.
76	Providing supplying and fixing to walls 6mm thick mirror and wall papers of best quality including material ,drilling of holes ,bolt and nuts arrengements ,grinding polishing all lift and lead ,labour transportion etc complet as per direction engineer incharge of work
77	Providing, supplying and fixing of lockers for changing rooms, special lighting systems for gym 81 other areas and music system with speakers for gym area.
E1	KSRB 14.9-2 : Providing and laying M-15 cement concrete flooring 60 mm thick with metallic concrete hardner toping, under layer of 45mm thick M-15 cement concrete using broken granite metal of 20mm and down size and top layer of 15mm thick metallic cement hardner consisting of mix 1:2 (1 cement hardner mix : 2 granite metal 10mm nominal size) by volume, with metalic hardening compound of approved quality mix in the ratio of 4:1 (4 part of cement = 1 part of metallic floor hardening compound of approved quality by wt) , including finishing, cost of materials, labour, curing, complete as per specification
E2	KSRB 3.5: Providing, injecting chemical emulsion for **Pre-constructional Anti-Termite Treatment** of soil under **existing floors** using chemical emulsion at one litre / hole 30mm apart including drilling 12mm. dia holes and plugging with cement mortar 1:2 proportion to match with the existing floors with chlorophyriphos emulsion concentrate 20%, including cost of chemical diluting in water to one percent concentration, labour, HOM of equipments, complete as per specifications.
E3	Supplying box type suitable for 28W T5 single / twin Lamp & suspension mounted luminaire & optical reflector. Prewired with HF electronic Ballast, push fit type lamp holders & main connectors. Channel cover shall be made of CRCA MS Sheet and finishing is done with stove enameled white with end caps made of engineering plastic. **1x4'-28 Watts**
E4	Supply of 2'x2' LED recessed luminaries with ...Watts system wattage. Housing shall be with pressure die cast aluminum alloy with corrosion proof resistant polyester power coated. Driver operates with voltage range from 100V to 270V 50/60 Hz with short circuit, overload & mis-wiring protection. Lumen Maintenance of 70% at 50000 Hrs. Injection moulded poly carbonate diffuser for better mechanical stability, light transmission & avoid pot hole effect. Junction temperature shall be < 70 degree Celsius. Driver is on constant current driver @ 0.06A with PF > 0.92 with line voltage @ 220-240V @ 50/60Hz, driver efficiency > 85% & THD<15%. LED Efficiency > 130 lm/W at 1W & Fixture Efficiency >75lm/w with CRI > 75 with injection moulded Polycarbonate lens with < 80mm depth. 5 years Warranty against any manufacturing defect working under standard electrical condition. **LED modular down light 2'x2'-55 watts**
	Total

CERTIFICATE :

1. Certified that the above work done satisfactory and no materials issued from departmentally.

Scanned by CamScanner

Previous Measurement		Present Measurement			Total Upto Date		Remarks
Qty.	Cost	Qty.	Rate Rs. P.	Amount	Qty	Cost	
-	-	2.00	28000.00	56000.00	2.00	56000.00	
-	-	5.00	56000.00	280000.00	5.00	280000.00	
-	-	1.00	526400.00	526400.00	1.00	526400.00	
-	-	1841.23	770.45	1418576.00	1841.23	1418576.00	
-	-	1841.23	862.82	1588650.00	1841.23	1588650.00	
-	-	400.00	1108.70	443480.00	400.00	443480.00	
-	-	70.00	10384.83	726938.00	70.00	726938.00	
				15736637.00		15736637.00	

Rs: 1,57,15980- Rs: 1571598.0-

AE-9 13/08/2018

Assistant Executive Engineer
Vidyaranyapura Sub Division
BBMP, Bangalore - 97

Scanned by CamScanner